

AXIS FA54 Main Unit

Video		Pre- and post-alarm video buffering Video and audio recording to edge storage, play audio clip, external output activation
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	
Resolution	1920x1080 (1080p) to 480x270	
Wide dynamic range	Forensic WDR	
Frame rate	In 1080p: 25/30 fps (50/60 Hz)	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264 Quad view, max 1080p resolution HDMI	
HDMI output	Single camera source Quad view Playlist: single camera sources, still images 1080p 30/25/24 fps (50/60 Hz) 720p 50/60 fps (50/60 Hz) 576p 50 fps (50/60 Hz) 480p 60 fps (50/60 Hz)	
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure value, exposure control, exposure zones, local contrast, rotation, Corridor Format, text and image overlay, privacy mask, mirroring of images	
Audio		
Audio streaming	Two-way, full duplex and half duplex	
Audio compression	AAC-LC 8/16/32/48 kHz, max 128 kbit/s G.711 PCM 8 kHz 64 kbit/s G.726 ADPCM 8 kHz 32 kbit/s or 24 kbit/s Opus 8/16/48 kHz, max 128 kbit/s Configurable bit rate	
Audio input/output	External microphone input or line input, line output	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at www.onvif.org	
Analytics	Included AXIS Video Motion Detection Active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, www.axis.com/acap	
Event triggers	Analytics, external inputs Edge storage events	
Event actions	File upload: email, FTP, HTTP, HTTPS, network share Notification: email, HTTP, HTTPS and TCP	
Built-in installation aids	Pixel counter	
Data streaming	Event data	
General		
Casing	Aluminum Plastic	
Sustainability	PVC free	
Memory	1024 MB RAM, 512 MB Flash	
Power	12 V DC, typical 14 W, max 30 W	
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T RJ12 for sensor units 6-pin terminal block for four configurable inputs/outputs (12 V DC output), max load 50 mA Two 3.5 mm mic/line in, 3.5 mm line out DC connector for 12 V DC input HDMI type A	
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations, see www.axis.com	
Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10-85% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, ICES-003 Class A Safety IEC/EN/UL 62368-1 Environment EN 50581, IEC 60529 IP3X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC 60068-2-6, IEC 60068-2-27	
Dimensions	202 x 102 x 31 mm (7 15/16 x 4 x 1 1/4 in)	
Weight	442 g (0.98 lb)	
Included accessories	Installation Guide, Windows decoder 1-user license, power supply Rubber feet, mounting brackets	
Optional accessories	AXIS F7315 Cable White 15 m For more accessories, see www.axis.com	
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:
www.axis.com/environmental-responsibility